

ELECTRIC SCISSOR LIFTS

GTJZ0608S (1930S)

Compliant with CE/ANSI/CSA/KCS/AS/EAC standards

PRODUCT HIGHLIGHTS

Efficient And Environmentally Friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot for efficient equipment transportation
- Folding guardrails for easy transport

Reduced Maintenance Costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- High quality parts and components

More Reliable Performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system guarantee safety of operation



Standard Features

2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Auto braking system
Horn & buzzer		

Options & Accessories

RCBO	AC power to platform	Platform work light
Footswitch	Overhead anti-collision device	Track unit
Lithium battery		

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SCISSOR LIFTS GTJZ0608S (1930S)

Compliant with CE/ANSI/CSA/KCS/AS/EAC standards

Model	GTJZ0608S (1930S)
Dimensions	
Max Working Height (Indoor/Outdoor)	7.8 m (25'7")
A Max Platform Height (Indoor/Outdoor)	5.8 m (19')
B Platform Extension	0.9 m (3')
C Length-Stowed	1.78 m (5'10.1")
D Width-Stowed	0.76 m (2'6")
E Height-Stowed (Rails Folded)	1.86 m (6'1")
E Height-Stowed (Rail Unfolded)	2.12 m (6'11.5")
F Wheelbase	1.325 m (4'4.2")
Ground Clearance (Pothole Guard Stowed)	0.073 m (3")
Ground Clearance (Pothole Guard Deployed)	0.024 m (0.95")
Platform Dimensions (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")
Performance	
Platform Capacity	230 kg (507 lbs)
Extension Platform Capacity	120 kg (265 lbs)
Platform Allowable Occupants (Indoor/Outdoor)	2 Persons (ndoor Only)
Drive Speed (Stowed)	0~3 km/ h (0~1.86 mph)
Drive-Speed (Raised)	0~0.8 km/ h (0~0.5 mph)
Lift Time (Unloaded)	15 s~20 s
Lower Time (Unloaded)	25 s~30 s
Gradeability	25%
Max Allowable Inclination (Front-To-Back/Side-To-Side)	3°/1.5°
Turning Radius (Inside/Outside)	0 m/1.49 m (0/4'10.7")
Tire Size/Type	305×115 mm (12×4.5")/solid
Power	
Drive×Steer	2 WD×2 WS
Power Source (V/kW)	24 V DC /3.3 kW
Hydraulic Tank Capacity	9 L (2.0 gal (UK) /2.4 gal(US))
Batteries	24 V,220Ah (Lead Acid Battery) 25.6V,156 Ah (Lithium Battery)
Charger (Input/Output)	100~240 V AC/30A
Weight	
Weight (Indoor/Outdoor)	1,526 kg (3,365 lbs) (Indoor Only)
Standards Compliance	CE/ANSI/CSA/KCS/EAC

